



Safely connecting the world!

		- 2		8	
SAFE no.	Description	Dimension. L=Thread length (mm)	Qty/pack	Recommended Ceramic Ferrule	Notes
SAFE no.				Ceramic Ferrule	And A
6AFE no.		L=Thread length (mm)		Ceramic Ferrule	And A
	For non-electron	L=Thread length (mm)	(brazing	Ceramic Ferrule	And A
1001	For non-electron 8mm Standard	L=Thread length (mm) ic pinbrazing equipment Ø8mm	(brazing	Ceramic Ferrule pins with fuse 2003	And A
1001 1010	For non-electron 8mm Standard 8mm Extra Silver 9,5mm	L=Thread length (mm) ic pinbrazing equipment Ø8mm Ø8mm	(brazing 100 100 100	Ceramic Ferrule pins with fuse 2003 2003 2009	wire)
1001 1010	For non-electron 8mm Standard 8mm Extra Silver 9,5mm	L=Thread length (mm)         ic pinbrazing equipment         Ø8mm         Ø8mm         Ø9,5mm	(brazing 100 100 100	Ceramic Ferrule pins with fuse 2003 2003 2009	wire)
1001 1010 1013	For non-electron 8mm Standard 8mm Extra Silver 9,5mm Threaded brazing pin	L=Thread length (mm) ic pinbrazing equipment Ø8mm Ø8mm Ø9,5mm s for non-electronic pinb	(brazing 100 100 100	Ceramic Ferrule pins with fuse 2003 2003 2009	ic thread)

## Safetrack Baavhammar AB

Möllebergavägen 339-24, 245 93 Staffanstorp, Sweden +46 (0)40 44 53 00 www.safetrack.se sales@safetrack.se