HJULFLÄNSMÄTARE

Precisionsinstrument för mätning av höjd, tjocklek och slitage på hjulflänsar



- **Tre mätparametrar**

  Flänshöjd (Sh), flänstjocklek (Sd) och flänsslitage (Qr).

- **Avläsning med 0,1 mm**

  Tydliga analoga skalor för noggrann kontroll av flänsprofilen.

- **Magnetisk fastsättning**

  Kan enkelt placeras och fixeras på hjulet under mätning.

- **För verkstad och fält**

  Robust instrument för kontroll och underhåll av järnvägshjul.

Denna hjulflänsmätare är ett precisionsinstrument för kontroll av järnvägshjulens flänsprofil. Instrumentet används för att mäta flänshöjd, flänstjocklek och flänsslitage. Magnetisk fastsättning gör det enkelt att placera och fixera instrumentet på hjulet, medan den robusta konstruktionen och de tydliga skalorna underlättar mätning i både verkstad och fält.

Tekniska specifikationer

Flänshöjd (Sh)	15–36 mm
Flänstjocklek (Sd)	22–36 mm
Flänsslitage (Qr)	6–10 mm
Avläsningsnoggrannhet	0,1 mm
Fastsättning	Magnetisk
Avläsning	Analog skala
Användning	Kontroll och underhåll av hjulflänsprofiler

Standardreferenser enligt underlaget

EN 13715:200 / UIC 510-1, 510-2, 514-1 / DIN 862

Safetrack Baavhammar AB
Möllebergavägen 339-24, 245 93 Staffanstorp, Sweden
+46 (0)40 44 53 00 www.safetrack.se sales@safetrack.se

SAFETRACK®
www.safetrack.se

ISO 9001 & 14001 Certified

Safely connecting the world!

Intertek

MM-325

WHEEL FLANGE GAUGE

Precision instrument for measuring wheel flange height, thickness and wear



- **Three measurements**

  Flange height (Sh), flange thickness (Sd) and flange wear (Qr).

- **0.1 mm reading accuracy**

  Clear analogue scales for accurate checks of the flange profile.

- **Magnetic attachment**

  Easy positioning and secure fixation to the wheel during measurement.

- **Workshop and field use**

  Robust instrument for railway wheel inspection and maintenance.

This precision wheel flange gauge is designed to check the flange profile of railway wheels. It measures flange height, flange thickness and flange wear. Magnetic attachment allows easy positioning and fixation on the wheel during measurement, while its robust construction and clearly marked scales make it suitable for inspections in workshops and in the field.

Technical specifications

Flange height (Sh)	15–36 mm
Flange thickness (Sd)	22–36 mm
Flange wear (Qr)	6–10 mm
Reading accuracy	0.1 mm
Attachment	Magnetic
Readout	Analogue scale
Application	Railway wheel flange inspection and maintenance

Standards referenced in supplied information

EN 13715:200 / UIC 510-1, 510-2, 514-1 / DIN 862

Safetrack Baavhammar AB
Möllebergavägen 339-24, 245 93 Staffanstorp, Sweden
+46 (0)40 44 53 00 www.safetrack.se sales@safetrack.se